

Enclosed Tray Delivery Cart

D Series - Side Loaded

ALLIANCE PRODUCTS

High-value stainless steel and aluminum equipment

Specifications

- Stainless steel is nickel-bearing, 200 series minimum. This material is NSF recognized for corrosion resistance.
- 18 gauge stainless steel body and doors.
- 16 gauge stainless tray slides with 14 gauge uprights.
- 16 gauge bottom and top.
- Double pan door with 1" rigid fiberglass insulation for sound deadening.
- Door mounted on stainless steel lift off hinges which allow 270 degree door swing.
- Stainless steel flush mount paddle latch.
- Non-marking vinyl perimeter bumper.
- Vent louvers in cart sides and back.
- Floor drains.
- 8" diameter cushion casters (two swivel with manual brakes, two rigid casters without brakes) on two door models.
- 6" diameter casters on single door models.
- Removable and adjustable tray slides accommodate either 14" x 18" or 15" x 20" trays at 5" spacing.
- Ledges are 2" wide.

Options

- 8" diameter casters for single door models.
- Please contact our facility at 615-895-5333 with inquiries for custom tray sizes, capacities, and ledge spacing.



Enclosed Tray Delivery Cart

D Series - Side Loaded

Customization is available

Dimensions - Examples of Previous Models

Model	Tray Capacity		Ledge Spacing	# of Interior Compartments	Overall Size			Casters		Shipping Weight	Case Cube
					W	D	H	Type	Dia.	lbs.	Cu. ft.
D18TC	18 ea.	14"x18" or 15"x20"	5"	1	26 1/8"	36 3/4 "	56"	2 swivel, 2 fixed	6"	300	37.6
D20TC	20 ea.	14"x18" or 15"x20"	5"	1	26 1/8"	36 3/4 "	61"	2 swivel, 2 fixed	6"	320	40.8
D24TC	24 ea.	14"x18" or 15"x20"	5"	2	51 1/8"	34 1/4"	41"	2 swivel, 2 fixed	8"	425	50.9
D28TC	28 ea.	14"x18" or 15"x20"	5"	2	51 1/8"	34 1/4"	46"	2 swivel, 2 fixed	8"	450	57.8
D32TC	32 ea.	14"x18" or 15"x20"	5"	2	51 1/8"	34 1/4"	51"	2 swivel, 2 fixed	8"	475	63.6

Drawings

